



Close window to  
exit NSF Listings.

## NSF Product and Service Listings

These Listings were Last Updated on **Monday, January 11, 2010** at 4:15 AM Eastern Time.  
Please [contact NSF International](#) to confirm the status of any Listing, report errors, or make suggestions.

**Warning: NSF is concerned about fraudulent downloading and manipulation of website text. If you have received this listing in hard copy, always confirm this certification/listing information by going directly to <http://www.nsf.org/Certified/Plumbing/Listings.asp?Company=3C870&> for the latest most accurate information.**

### MP Mechanical Plumbing Products

#### GOSLYN LP

1536 LANTERN TRAIL  
FRISCO, TX 75034  
972-562-1113

[Visit this company's website](#)

**Facility :** SHANGHAI, CHINA

Product Type	Material Type	Trade Name	Product Standard
<i>Grease and Oil Separator# *MLTPL</i>		<i>GOS 80</i>	<i>CSA B481.1</i>
<small># Tested and rated as Type A: Units with an external flow control, with air intake (vent): directly connected. * Flow Rate: 25 GPM.</small>			
<i>Grease and Oil Separator# %</i>	<i>MLTPL</i>	<i>GOS 40</i>	<i>CSA B481.1</i>
<small># Tested and rated as Type A: Units with an external flow control, with air intake (vent): directly connected. % Flow Rate: 10 GPM.</small>			
<i>Grease and Oil Separator# %§</i>	<i>MLTPL</i>	<i>GOS 40</i>	<i>ASME A112.14.3</i>
<small># Tested and rated as Type A: Units with an external flow control, with air intake (vent): directly connected. % Flow Rate: 10 GPM. § Product is Certified to the Uniform Plumbing Code™. Installation in accordance with the manufacturer's instructions and the requirements of the latest edition of the Uniform Plumbing Code™.</small>			

*Grease and Oil  
Separator# \* §*

*MLTPL*

*GOS 80*

*ASME A112.14.3*

# Tested and rated as Type A: Units with an external flow control, with air intake (vent):  
directly connected.

\* Flow Rate: 25 GPM.

§ Product is Certified to the Uniform Plumbing Code™. Installation in accordance with the  
manufacturer's instructions and the requirements of the latest edition of the Uniform  
Plumbing Code™.

*Grease and Oil  
Separator% §*

*MLTPL*

*GOS 40*

*ASME A112.14.4*

% Flow Rate: 10 GPM.

§ Product is Certified to the Uniform Plumbing Code™. Installation in accordance with the  
manufacturer's instructions and the requirements of the latest edition of the Uniform  
Plumbing Code™.

*Grease and Oil Separator\* §MLTPL*

*GOS 80*

*ASME A112.14.4*

\* Flow Rate: 25 GPM.

§ Product is Certified to the Uniform Plumbing Code™. Installation in accordance with the  
manufacturer's instructions and the requirements of the latest edition of the Uniform  
Plumbing Code™.

---

Number of matching Manufacturers is 1

Number of matching Products is 6

Processing time was 0 seconds

- [Search Listings](#) |
- [News Room](#) |
- [About NSF](#) |
- [Careers](#) |
- [NSF Mark](#) |
- [Client Log-In](#)
  
- [Privacy Policy](#) |
- [Site Map](#) |
- [Request Info](#) |
- [Contact Us](#) |
- [Copyright © 2004 NSF International.](#)